

MATERIAL SAFETY DATA SHEET

TROJAN CHEMICALS
4 BLAIR DRIVE
BRAMPTON, ONTARIO
L6T 2H5
TEL# (905) 456-9444

EMERGENCY # CANUTEC (613) 996-6666
"USE IN CASE OF CHEMICAL EMERGENCY ONLY"

W.H.M.I.S. CLASSIFICATION: B3

MATERIAL REFERENCE NO: 619900 SECTION I - MATERIAL IDENTIFICATION AND USE _____ |MATERIAL NAME/I.D.: TRL-199 ______ | CHEMICAL NAME: NOT AVAILABLE | CHEMICAL FAMILY: LUBRICANTS ______ |CHEMICAL FORMULA: MIXTURE |MOLECULAR WEIGHT: NOT APPLICABLE| |SYNONYMS: NONE |MATERIAL USE: SILICONE LUBRICANT SECTION II - HAZARDOUS INGREDIENTS OF MATERIAL _____ |MINERAL SPIRITS | 60.0-100.0 | 175 | 68551-17-7 | 3460 MG/KG | SECTION III - PHYSICAL DATA FOR MATERIAL |PHYSICAL STATE: LIQUID _____ ODOUR AND APPEARANCE: COLOURLESS LIQUID, PETROLEUM ODOUR. |ODOUR THRESHOLD (PPM) | SPECIFIC GRAVITY | VAPOUR PRESSURE (MM) | NOT ESTABLISHED | 0.791 | NOT AVAILABLE | _____ |VAPOUR DENSITY (AIR=1)| EVAPORATION RATE |SOLUBILITY IN WATER | BOILING POINT (C) | FREEZING POINT (C) |% VOLATILE (BY WEIGHT)| INITIAL 157 | <1 | >95 | | DENSITY (G/ML) | COEF.OF WATER/OIL DISTR| NOT APPLICABLE | NOT APPLICABLE | NOT AVAILABLE |



MATERIAL REFERENCE NO: 619900

SECTION IV - FIRE AND EXPLOSION HAZARD OF MATERIAL
FLAMMABILITY: COMBUSTIBLE IF YES, UNDER WHICH CONDITIONS: CONTACT WITH DIRECT IGINITION SOURCE (OPEN FLAME)
MEANS OF EXTINCTION: CO2, DRY CHEMICAL, ALCOHOL FOAM, WATER FOG.
SPECIAL PROCEDURES: WEAR FULL PROTECTIVE EQUIPMENT, INCLUDING SELF- CONTAINED BREATHING APPARATUS FOR ALL CHEMICAL FIRES.
FLASH POINT (C) AND METHOD: MINIMUM 43 (C) (TCC)
HAZARDOUS COMBUSTION PRODUCTS: CARBON DIOXIDE, CARBON MONOXIDE, UNIDENTIFIED ORGANIC COMPOUNDS, BLACK SMOKE.
UPPER EXPLOSION LIMIT LOWER EXPLOSION LIMIT AUTOIGNITION TEMP(C) NOT AVAILABLE NOT AVAILABLE
EXPLOSION DATA SENSITIVITY RATE OF BURNING EXPLOSIVE POWER TO CHEMICAL IMPACT
SENSITIVITY TO STATIC DISCHARGE: NOT AVAILABLE
SECTION V - REACTIVITY DATA CHEMICAL STABILITY: STABLE IF NO, UNDER WHICH CONDITIONS:
INCOMPATIBILITY TO OTHER SUBSTANCES: YES IF SO, WHICH ONES: STRONG OXIDIZERS.
REACTIVITY AND UNDER WHAT CONDITIONS: NOT ESTABLISHED
HAZARDOUS DECOMPOSITION PRODUCTS: OXIDES OF CARBON, TOXIC FUMES/VAPOURS, SMOKE.
SECTION VI - HEALTH HAZARD DATA
ROUTE OF ENTRY:
SKIN CONTACT: YES



MATERIAL SAFETY DATA SHEET

MATERIAL REFERENCE NO: 619900 ______ |EFFECTS OF ACUTE EXPOSURE TO MATERIAL: |EYES-MAY CAUSE SLIGHT IRRITATION. | SKIN-CONTACT MAY CAUSE DRYING, CRACKING WITH IRRITATION. | INHALATION-EXCESSIVE INHALATION OF HIGH CONCENTRATIONS OF VAPOURS |MAY CAUSE IRRITATION OF RESPIRATORY TRACT, HEADACHES, DIZZINESS, | ANETHESIA, DROWZINESS AND OTHER CENTRAL NERVOUS SYSTEM EFFECTS. | INGESTION-MAY CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING. |ASPIRATION OF SMALL AMOUNTS INTO LUNGS MAY CAUSE MILD TO SEVERE | PULMONARY INJURY. ._____ | LEFFECTS OF CHRONIC EXPOSURE TO MATERIAL: | SKIN-PROLONGED OR REPEATED CONTACT MAY CAUSE SKIN RASH (DERMATITIS). _____ |LD 50 OF MATL. |LC 50 OF MATL. |EXPOSURE LIMIT(S)|IRRITANCY OF MATL| NOT AVAILABLE | NOT AVAILABLE | MODERATE | | SENSITIZATION OF MATERIAL | SYNERGISTIC MATERIALS | NOT AVAILABLE | NOT AVAILABLE -----|CARCINOGENICITY, REPRODUCTIVE EFFECTS, TERATOGENICITY, MUTAGENICITY | | NONE KNOWN. SECTION VII - PREVENTIVE MEASURES ______ | PERSONAL PROTECTIVE EQUIPMENT: GLOVES: APPROPRIATE CHEMICAL RESISTANT. | RESPIRATORY: NOT NORMALLY REQUIRED. FOR PROLONGED EXPOSURES OR IF TLV IS EXCEEDED, USE NIOSH APPROVED RESPIRATOR. EYE: SAFETY SHIELD OR GOGGLES IF EYE CONTACT IS LIKELY. FOOTWEAR: NO SPECIAL REQUIREMENTS. CLOTHING: NO SPECIAL REQUIREMENTS. OTHER: EYE WASH, SAFETY SHOWER. | ENGINEERING CONTROLS (EG VENTILATION, ENCLOSED PROCESS): MECHANICAL | VENTILATION IN CONFINED AREAS OR WHEN TLV IS EXCEEDED. | ______ LEAK AND SPILL PROCEDURE: WEAR RECOMMEDED PROTECTIVE EQUIPMENT. REMOVE SOURCES OF IGNITION. CONTAIN SPILL. PROVIDE ADEQUATE | VENTILATION. TRANSFER SPILLED MATERIAL INTO A METAL CONTAINER FOR | REUSE OR DISPOSAL. ABSORB REMAINING MATERIAL ONTO VERMICULITE OR |SAWDUST AND PLACE IN METAL CONTAINER FOR DISPOSAL. ______ |WASTE DISPOSAL: DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, PROVINCIAL | IAND FEDERAL REGULATIONS.



MATERIAL SAFETY DATA SHEET

MATERIAL REFERENCE NO: 619900

SECTION VIII - FIRST AID MEASURES IPROCEDURES: | EYES- FLUSH WITH RUNNING WATER FOR AT LEAST 15 MINUTES WHILE HOLDING | EYELIDS OPEN. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. | SKIN-REMOVE CONTAMINATED CLOTHING. FLUSH WITH WATER FOR AT LEAST 15 | |MINUTES. GET MEDICAL ATTENTION IF IRRITATION PERSISTS. | INHALATION-REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, GIVE OXYGEN. IF NOT BREATHING ADMINISTER ARTIFICIAL RESPIRATION AND GET | IMMEDIATE MEDICAL ATTENTION. | INGESTION-IF SWALLOWED DO NOT INDUCE VOMITING. GET IMMEDIATE IMEDICAL ATTENTION. | SOURCES USED: RAW MATERIAL SUPPLIER'S MATERIAL SAFETY DATA SHEETS. |ADDITIONAL INFORMATION: NONE SECTION IX - TDG SHIPPING INFORMATION SHIPPING NAME | CLASS | UN NO. | PACKING GROUP | | FLAMMABLE LIQUID N.O.S. | 3 | (PETROLEUM DISTILLATES) | 1993 | NOT REGULATED BY ROAD OR RAIL IN CONTAINERS OF LESS THAN 450 L. ______ | HANDLING PROCEDURES AND EQUIPMENT: AVOID CONTACT WITH SKIN AND EYES. | | WASH THOROUGHLY AFTER HANDLING. |STORAGE REQUIREMENTS: STORE IN A COOL, DRY, WELL-VENTILATED AREA. KEEP CONTAINER CLOSED WHEN NOT IN USE. |SPECIAL SHIPPING INFORMATION: NONE SECTION X - HMIS HAZARD RATING INFORMATION _____ FLAMMABILITY | REACTIVITY | HEALTH 0 1 SECTION XI - PREPARATION DATE OF MSDS ______ | PREPARED BY: TECHNICAL DEPARTMENT TELEPHONE # (905) 456-9444 |REVIEWED: OCTOBER 11, 2009

DISCLAIMER:

THE INFORMATION CONTAINED HEREIN IS COMPILED FROM SOURCES BELIEVED TO BE RELIABLE. THE MANNER AND CONDITIONS OF USE AND HANDLING MAY INVOLVE OTHER AND ADDITIONAL CONSIDERATIONS. WE ACCEPT NO RESPONSIBILTY FOR THE ACCURACY, SUFFICIENCY, RELIABILITY OR FOR ANY LOSS OR INJURY RESULTING FROM THE USE OF THE INFORMATION.