

TRL-199

		Silicone Dry Lubricant
W	DESCRIPTION:	Liquid, colourless, typical odour.
ıt	USED FOR:	Lubricating and preventing sticking, binding and squeaking, as well as beautifying, water proofing and protecting.
icaı		TRL 199 is used on metal, glass, rubber, plastic, painted finishes, fabrics and on food machinery, automobiles, in manufacturing plants, printing, paper, textile, sewing, food processing and packaging industries.
Lubricants	SPECIAL BENEFITS:	Easy to apply. Ready to use. Safe on all surfaces and fabrics. Non-staining. Non-toxic when used as directed. Safe for equipment contacting food products. Retards rust and corrosion. Stable to heat and cold - (- 40 C to +204 C).
Specialty	DIRECTIONS:	Minimizes dirt build-up in cracks. Low surface tension properties. Dries fast. Treated surfaces and parts, slide and glide easier without grease. Not affected by water, oil or most solvents. Speeds up cleaning of food processing and kitchen equipment. Spray and deposit a light film on previously cleaned surfaces. Use a sweeping motion to spray and apply. Re-apply as required. Always spray on a clean surface. TRL 199 is available in aerosol as TRB 599
	Package Size: (code)	210 L 619916 120 L 619914 20 L 619911 4x4 L 619906